

DECLARATION OF PERFORMANCE

SalzXL1-CRP-2013/11/15-GB



PRODUCT

| | |
|------------------------|---|
| Product type | Slow heat release appliance |
| Type designation | Salzburg XL+1 |
| Product identification | See product instruction manual |
| Intended area of use | Heating of rooms in residential buildings |
| Fuel | Wood |

MANUFACTURER

| | |
|---------|---|
| Name | Nordpeis AS |
| Address | Gjellebekkstubben 11 3420 Lierskogen, Norway |

CHECKS

| | |
|----------------------------|--|
| According to AVCP Standard | System 3 EN 15250:2007 |
| Test institute | Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625 has checked declared performance and issued test report no. RRF- 50 12 3042 |

DECLARED PERFORMANCE

| Essential Characteristic | Performance | Harmonized technical specification |
|---|--|------------------------------------|
| Reaction to fire | A1 WT | EN 15250:2007 |
| Minimum distances to combustible material | 70 mm rear 150 mm side other safety distances according product manual | |
| Risk of falling embers | Approved | |
| Emission from combustion: Carbon monoxide at 13% O ₂ Oxygen nitride NOx at 13% O ₂ Organic Gaseous Carbon at 13% O ₂ Particulate Matter at 13 O ₂ | CO = 0,100 % Vol NOx = 109 mg / m ³ OGC = 89 mg / m ³ PM = 24 mg / m ³ | |
| Surface temperatures | Approved | |
| Cleanability | Approved | |
| Mechanical durability | Approved | |
| Releases of Hazardous Substances | Approved | |
| Total thermal output | 88,6 kWh | |
| Nominal output after elapsed time at 25% of max. mean temperature | P = 4,10 kW | |
| Flue gas temperature at nominal output | t _a = 114 °C | |
| Energy efficiency | η = 89,0 % | |

The undersigned is responsible for the manufacture and conformity with declared performance



Stian Varre, CEO Nordpeis AS